

It's not just what it does. It's what it does for you.

















Key Features

- Transform NCR Interactive Assisted Teller enabled. Connect consumers to the efficient delivery of convenient live teller services from their vehicle across flexible hours and locations.
- Attract Infinity Display: supports multi-touch. 15" or 19"
 LCD screen. Integrated customized branding opportunities for financial institutions.
- Engage Supports NCR CxBanking SW platform includes personalization and targeted marketing opportunities. Enable the omni-channel experience. Engage mobile first consumers.
- Available Enhanced ATM module reliability via Media Handling 2.0. Flexible, future-proofed dispense, deposit and recycling options. Performance enhanced durable design.
- Manage Service intervention process improvements. Full range of common parts across all solutions. Improved device level intelligence.
- Security designed in for more effective risk management and fraud prevention. Includes: strengthened shutter, cash/ consumer camera and new flush SPS card reader.

Technical Specifications

PRODUCT DIMENSIONS

HEIGHT 59.57" (1,513mm)*
 WIDTH 30.31" (770mm)*

• DEPTH

Long sleeve 49.13" (1,248mm) Short sleeve 44.65" (1,134mm) • WEIGHT 2,052lbs (931kg) CEN III/IV safe 2,371lbs (1,076kg)

CONSUMER INTERFACE

- Infinity Display Supports multi-touch 15" or 19" brightened color LCD screen
- Media Entry/Exit Indicators Dynamic active customizable color LEDs.
 Directional and pulsing user guidance MEIs.
- Lighting Task lighting. Ambient light sensing.
- PIN Pad Recessed Encrypting (Polycarbonate or stainless steel)
- Card Reader EMV Ready.
 (Dip, Motorized IMCRW)
- Contactless enabled
 Integrated Reader (via card, smartphone or smartwatch)
- Audio Public/Private. Enhanced speakers. Noise cancelling microphone.

MEDIA HANDLING 2.0 TECHNOLOGY

- Dispense S2 Media Dispense Module: up to 60 note bunch, 2,500 notes per cassette** Up to 25,000 note capacity (5 high)** Vacuum based with adaptive media picking technology.
- Deposit SDM2: up to 100 mixed media bunch cash + check in a single transaction. Store up to 4,000 notes + 400 checks** 4-way bundle orientation. Two storage variants.

 Recycle/Deposit – GBxx2: up to 200 notes per transaction. Store up to 2,300 notes per cassette (deposit). Up to 2,000 notes (recycle)** Enhanced note pre-acceptor and separator

PRINTER OPTIONS

 Thermal Receipt/Journal Printer, options – Dual roll and 2ST

SECURITY

- Supports "Picture in Picture" security
- Privacy filter enabled display
- Cameras 3rd party consumer camera and optional cash slot camera enabled
- SolidCore Software Suite for APTRA™
- Trusted Platform Module enabled
- Strengthened Secure Shutter (SSS)
- Integrated "flush" Skimming Protection Solution (SPS)
- UL437 Topbox lock
- Safes CEN I, CEN III, CEN III GasEx, CEN IV GasEx options. Safe Heater with S2

ENVIRONMENTAL

- Standard -31°F to 122°F (-35°c to 50°c).
- Humidity 10% TO 100%.
- Acoustics 65dB (A) idle 68dB operating.
 Max 75dB (A) fan
- Severe environment protection kit

SERVICING

- Front/rear/side access
- LCD Operator Panel (GOP or COP) rear load only
- State of health indicators across all modules

OPERATING PLATFORM

- PC Core with Intel® i5 processor
- 8GB RAM. 240GB Solid State Hard Drive
- DVD-RW Drive

SOFTWARE

- Microsoft Windows® 7 Professional
- NCR APTRA XFS
- Supports NCR CxBanking SW platform

ADDITIONAL FEATURES

- Barcode reader 2D Barcode supports 1D/2D documents (Sidecar Option)
- e-Receipts to a mobile device
- UPS (Uninterruptable Power Supply)
- NCR Interactive Banker and Teller Enterprise SW compatible
- * Dependent on check or note quality, thickness and deposit module used. Capacity may vary by country, currency type, condition and quality of notes
- ** 5 High Dual-dispense





marks of their respective holders. Learn more at www.ncr.com

countries. All brand and product names appearing in this document are trademarks, registered trademarks or service